


NOTES -

1- WHEN REQ'D, FOR MATING CONNECTORS, INCLUDE:

D/E PIN # A 24260 } INCL STRAIN RELIEF  
 DE PIN # V 24260 }

ENVIRONMENTAL CONDITIONS		QUALITY CONTROL TESTING	
TEMP.		THERMAL CYCLING	HRS PER CYCLE
PRESSURE		SAMPLING	
VACUUM		NO. OF CYCLES	
CHEMICALS		LOW TEMP	
OTHER		HIGH TEMP	
<b>HOUSING SPECIFICATIONS</b>		DPS 1060-3-3-0	
DE PART NO.	12392		
THREAD	1 3/4 - 18		
TYPE			
MATL	SS		
<b>CONSTRUCTION</b>			
INTERNAL	5294		
EXTERNAL			
POTTING	1469/1481		
<b>LEAD WIRE DATA</b>			
DE PART NO.	12182-20		
QTY OF COND	128		
AWG			
COND MATL			
STRANDING			
PLATING			
INSULATION			
VOLT RATING			
TEMP RATING			
SPECIFICATION			
COLOR CODE			
DESCRIPTION			

LEAD WIRE ENDS MAY BE STRIPPED 1/4 IN FOR TESTING

Drawn	EL	Date	5-24-91	 Ductorseal Insulated Feedthru <b>DOUGLAS ENGINEERING CO.</b> 14 Beach Street Rockaway, N.J. 07866 201-671-8230
App'd	DR	Date	7-2-91	
Do Not Scale Dwg				TITLE
UNLESS NOTED				<b>RBTR POTCON</b>
All Dimensions in Inches Remove All Burrs Break All Sharp Edges				size Dwg No
Tolerances: XX ± 0.1    XXX ± 0.05				<b>B (A/V) 24260</b>
Rev	ECN	App'd	Date	SCALE: NTS
REF	SPACE	BY	DATE	SHEET 1 OF 1

5017

Date:	11/10/08		
DEC Part Number:	24260		
Customer Name:	INFOTECH (CATALOG PART)		
CAR / RMA Reference:	CAR 648 / RMA 3389	Customer MRR/NCR	
Quality Instruction:	<p>LAST ORDER MADE FOR THIS PART NUMBER WAS MADE INCORRECTLY BECAUSE THE WRONG CONNECTOR WAS PULLED FOR THE JOB. STOCKROOM, PRODUCTION, QC, DID NOT REVIEW THE DRAWING IN ORDER TO DETERMINE THE WRONG CONNECTOR WAS USED.</p> <p>QC TO VERIFY THE CORRECT CONNECTOR IS USED.</p>		
	<b>REMOVE FROM DRAWING AFTER NEXT ORDER</b>		
Issued By:	R. DELLA TORRE		